







Microwave motion detector for escalators and moving walkways

## Straightforward, reliable, versatile

- One device for both internal and external applications
- Adjustable detection range and mounting methods
- Quick and easy startup





## **Technical data**

### Mechanical data

Material	ABS
Dimensions (mm)	$62 \times 48 \times 37 \text{ mm}$ (L × W × H)
Cable	Length 5 m, $5 \times 0.25$ mm <sup>2</sup>
Technological data	
Technology	Microwave Doppler Radar
Frequency	24.125 GHz
Transmitter radiated power (EIRP)	< 20 dBm
Max. detection distance	2.5 m
Detection mode	Motion
Min. detection speed	3 cm/s (measured in sensor axis)

Supply voltage	12~28 V AC ±10% 12~36 V DC ±10%
Frequency range	50–60 Hz
Max. power consumption	1.2 W
Output	Relay with switch-over contact
Rated load	0.5 A at 125 V AC; 1 A at 24 V DC
Rated carry current	2 A
Max. switching voltage	125 V AC, 60 V DC
Max. switching current	

Storage / operation temperature	-20°C to +60°C
Protection class	IP65

#### Note

Note Technical details and recommendations concerning our products are based on experience and are an aid for the orientation of the user. Details stated in our brochures and data sheets do not guarantee special properties of the product. This does not apply to special product properties confirmed by us in writing or individually. Subject to technical alterations.

# **Application**

### Situation


Escalator

#### Solution

CR3 restarts escalator when in energy-saving mode

### **Advantages**


- Compact housing allows for facile integration
- Easy adaption to application through adjustable detection range and different installation methods
- Optimised flow of people




### **Order details**

#### Article no. Description 362736 CR3 Microwave motion detector, black

# Mounting methods



Mounting from underneath



Mounting from rear



Stenhuggervej 2 5471 Søndersø Denmark Phone: +45 86 28 00 00 mail@swissdoor.dk www.swissdoor.dk

